

FAST CREW SUPPLIER 2610

532548



GENERAL

Hull material Aluminium Superstructure material Aluminium Basic functions Crew and cargo duties

Classification Bureau Veritas I № Hull • MACH

Light Ship / Fast Utility Vessel

Sea Area 3

Hung Hua Construction Co. Ltd. Owner

DIMENSIONS

Length overall 26.3 m 10.3 m Beam overall Depth at sides 3.7 m Draught max 2.4 m Deadweight max Up to 20.0 t Cargo deck area Deck load 100 0 m² 1.5 t/m² Deck cargo 15.0 t Gross tonnage 168 6 persons (Industrial) personnel 12 persons

TANK CAPACITIES

14.2 m³ 8.0 m³ Fuel oil Fuel oil trim 1.8 m³ Fresh water $0.5 \, \text{m}^3$ Sewage Bilge water/ dirty oil 0.4 m^{3}

PERFORMANCES

24.5 kn Range at max. speed 700 nm

PROPULSION SYSTEM

2x Caterpillar C32 TTA Main engines Total power 1,790 bkW 2x Reintjes ZWVS 440 Gearboxes Propulsion 2x Fixed pitch propeller 2x 50 kW, hydraulically driven Bow thrusters

ELECTRICAL EQUIPMENT

Network 24V DC, 400/230V 50Hz AC

Generator sets 2x 22.5 ekW

DECK LAY-OUT

1x 150 kg SHHP Pool TW, chain, electric winch Anchor equipment Heavy-duty bow fender, rubber "D" type at sides Fendering .

Moonpool Rescue zone

Foldable deck crane Heila HLM 20-2S

SHIP SYSTEMS

Ship systems are according to Class

2x pump, electrically driven Fuel trim system

Supply, 8,000 m³/hr each (one fan in each engine room) Engine room ventilation

Air-conditioning 70,000 BTU/hr

Novec 1230 in engine rooms Fire extinguishing

ACCOMMODATION

Bridge deck Wheelhouse, personnel area

Main deck Crew cabins, wet gear room, pantry, mess room, sanitary spaces Lower deck

Storage

NAUTICAL AND COMMUNICATION EQUIPMENT

Integrated navigation system Searchlight Radar 1x X-band **ECDIS**

1x AIS

Compass 1x Magnetic, 1x GPS Autopilot 1x

Echo sounder

Internal communications Intercom and loudhailer

External communications GMDSS A2

Weather system





FAST CREW SUPPLIER 2610

532548





