



## DP2 Multi Cat

Orient Supporter

The **First Choice** for  
Marine Solutions in  
Asia Pacific

For further information, please contact:  
[commercial@dfo.com.tw](mailto:commercial@dfo.com.tw)

### Principal Particulars

Built	2024
Length O.A.	33.0 m
Breadth MLD.	14.0 m
Depth at Side	4.55 m
Summer Draft	3.0 m
Gross Tonnage	486
Net Tonnage	145

### Classification

Bureau Veritas I ✕ HULL • MACH • AUT-UMS, DYNAPOS AM/AT R, Unrestricted Navigation, Tug, Special Service Multi Purpose vessel, Clean Ship-Ulev GMDSS Area A3

### Performance

Speed	10 knots
Bollard Pull	50 MT
Dynamic Positioning	Class 2

### Propulsion

Main Engines	3 x Caterpillar C32
Total Power	2,684 kW at 1800 RPM
Propellers	3 x 2,000 mm in nozzle

### Auxiliaries

Generator Sets	1 x Caterpillar C32 2 x Caterpillar C18 1 x Caterpillar C7.1
Total E-Power	1,596 kW
Hydraulic Power Pack	416 kW
Stern Thruster	2 x 300 kW
Bow Thruster	2 x 300 kW

### Accommodation

Facilities	Airconditioned accommodation for up to 16 persons.
Separate office space	
Separate recreation room	

### Tanks

Fuel Oil	200 m <sup>3</sup>
Fresh Water	30 m <sup>3</sup>

### Deck Lay-Out

Anchor Handling Winch	200 MT holding force
Pulling Force	150 MT at 1 <sup>st</sup> layer
Hauling Speed/Capacity	10 m/min – 30 m/min
Towing Winch	140 MT holding force
Pulling Force	50 MT at 1 <sup>st</sup> layer
Hauling Speed/Capacity	10 m/min–20 m/min 700 m/42 mm OD
Tugger Winch	15 MT at 1 <sup>st</sup> layer
Deck Crane Forward	HS Marine AKC 550, incl.15 Twinch
Deck Crane Aft	HS Marine AKC 370
Deck	Azobé deck covering
Towing Hook	60 MT
Towing Pins	Aft ship: manual set. Fore ship: hydraulic set + chain stopper
Fendering	Wood- and M-fendering on the side, pushbow fendering fore- and aft ship

### Options

4-Point Mooring System	4 hydraulic winches and anchors
Boatlanding	



Photos (front and back): Ein Dahmer, CC BY-SA 4.0, via Wikimedia Commons.